

AMENDMENTS TO THE CLAIMS

1. (Currently Amended) A method comprising:

recording a first node local time of receiving a wirelessly transmitted packet at a

first node, the first node local time recorded with a monotonically

increasing clock of the first node;

recording a second node local time of receiving the wirelessly transmitted packet

at a second node, the second node local time recorded with a

monotonically increasing clock of the second node;

wirelessly transmitting the first node recorded local time by the first node to at

least [[a]] the second node;

receiving the first node recorded local time at the second node and recording the

first node local time of receiving the wirelessly transmitted packet; and

synchronizing a second node timing model with a first node timing model, and

further synchronizing the first and second node timing models with a

global clock associated with the first node and the second node.
2. (Previously Presented) The method of claim 1, wherein the wirelessly transmitted
packet comprises a beacon transmitted from a wireless access point.
3. (Previously Presented) The method of claim 1, further including:

synchronizing sample numbers of a multimedia stream on the second node with

the second node timing model, the second node timing model having been

synchronized with the first node.

4. (Previously Presented) The method of claim 3, wherein the synchronization of sample numbers in I/O operations is performed by time-stamping IRQs request with a global time according to the global clock.
5. (Previously Presented) The method of claim 1, further including repeating the method of claim 1 to generate an updated second node timing model to synchronize with the first node timing model.
6. (Cancelled)
7. (Previously Presented) The method of claim 1, further includes:
recording a third node local time of receiving the wirelessly transmitted packet from the first node at a third node and recording the first node local time of receiving the wirelessly transmitted packet; and
synchronizing a third node timing model with the first node timing model and the second node timing model, and further synchronizing the first, second and third node timing models with the global clock associated with the first node, the second node, and the third node.
8. (Currently Amended) A machine-readable medium having stored thereon sets of instructions which when executed by a machine cause the machine to:
record a first node local time of receiving a wirelessly transmitted packet at a first node, the first node local time recorded with a monotonically increasing clock of the first node;

record a second node local time of receiving the wirelessly transmitted packet at
[[a]] the second node, the second node local time recorded with a
monotonically increasing clock of the second node;
wirelessly transmit the first node recorded local time by the first node to at least a
second node;
receive the first node recorded local time at the second node and record the first
node local time of receiving the wirelessly transmitted packet; and
synchronize a second node timing model with a first node timing model, and
further synchronize the first and second node timing models with a global
clock associated with the first node and the second node.

9. (Previously Presented) The machine-readable medium of claim 8, wherein the wirelessly transmitted packet comprises a beacon transmitted from a wireless access point.
10. (Previously Presented) The machine-readable medium of claim 8, wherein the sets of instructions when executed further cause the machine to:
synchronize sample numbers of a multimedia stream on the second node with the
second node timing model, the second node timing model having been
synchronized with the first node.
11. (Previously Presented) The machine-readable medium of claim 10, wherein the synchronization of sample numbers in I/O operations is performed by time-stamping IRQs request with a global time according to the global clock.

Claims 12-13 (Cancelled)

14. (Previously Presented) The machine-readable medium of claim 8, wherein the sets of instructions when executed further cause the machine to:
- record a third node local time of receiving the wirelessly transmitted packet from the first node at a third node and recording the first node local time of receiving the wirelessly transmitted packet; and
- synchronize a third node timing model with the first node timing model and the second node timing model, and further synchronize the first, second and third node timing models with the global clock associated with the first node, the second node, and the third node.
15. (Currently Amended) A system comprising:
- a first node to record a first node local time of receiving a wirelessly transmitted packet, the first node local time recorded with a monotonically increasing clock of the first node;
- a second node to record a second node local time of receiving the wirelessly transmitted packet at the second node, the second node local time recorded with a monotonically increasing clock of the second node;
- the first node to wirelessly transmit the first node recorded local time to at least [[a]] the second node;
- the second to receive the first node recorded local time and record the first node local time of receiving the wirelessly transmitted packet; and

the second node to synchronize a second node timing model with a first node timing model, and synchronize the first and second node timing models with a global clock associated with the first node and the second node.

16. (Previously Presented) The system of claim 15, wherein the wirelessly transmitted packet comprises a beacon transmitted from a wireless access point.
17. (Previously Presented) The system of claim 15, wherein the second node is further to:
synchronize sample numbers of a multimedia stream on the second node with the second node timing model, the the second node timing model having been synchronized with the first node.
18. (Previously Presented) The system of claim 17, wherein the synchronization of sample numbers in I/O operations is performed by time-stamping IRQs request with a global time according to the global clock.

Claim 19-20 (Cancelled)

21. (Previously Presented) The system of claim 15, further includes:
a third node to record a third node local time of receiving the wirelessly transmitted packet from the first node and record the first node local time of receiving the wirelessly transmitted packet; and

the third node to synchronize a third node timing model with the first node timing model and the second node timing model, and further to synchronize the first, second, and third node timing models with the global clock associated with the first node, the second node, and the third node.